

ACCEPTED BY THE HILLSDALE COUNTY SURVEY PEER GROUP AS THE OFFICIAL CORNER UNDER MICHIGAN PUBLIC ACT 345 OF 1980, 8-27-97A MEETING HELD ON Oct 9, 1997 AL REIMENBERG, CO. REP.

LIBER 3 PAGE 236 **128737** RECORDED
 HILLSDALE CO. MICH.
 REMONUMENTATION
7 NOV 26 PM 4 08
 LAND CORNER RECORDATION CERTIFICATE
 Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

<u>HILLSDALE</u> (County)	Located In:	Corner Code #
1. Public Land Survey	T <u>6S</u> R <u>1W</u>	<u>C-5</u>
	T _____ R _____	_____
	T _____ R _____	_____
	T _____ R _____	_____
2. Property Controlling in Section	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____
3. Miscellaneous Property in Sec.	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____
4. Lot No. _____, Recorded Plat _____		
5. Private Claims _____		

Justy VanZandt
 REG. OF DEEDS
SURVEY & REMONUMENTATION
FEB 11 1998
 Register of Deeds Stamp & File Number
SECTION

A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1						
3												
4	7	8	9	10	11	12						
5		•										
6	18	17	16	15	14	13						
7												
8	19	20	21	22	23	24						
9												
10	30	29	28	27	26	25						
11												
12	31	32	33	34	35	36						
13												

I, Jeffrey A. Bieszk, in a field survey on 12 November, 1997, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

GLO set by Robert Clark Jr. (1824)	LCRC (John Hatt L 1 P 337)
30" Beech N 68 E 16 lks	1/2" iron over stone
6" Beech N 63.5 W 19 lks	Power Pole NE 56.15 ft.
	SE COR. School Hse. 86.0 ft.
County Survey (George Marks 1882)	Iron is 8 ft. West of centerline of Road
Stake and Stone	
6" Tamarack N 59.5 E 37 lks	

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

John Hatt found stone in 1958 and set iron over stone, also found iron in 1973 and recorded this in his LCRC. I found iron as witnessed by John Hatt. Accepted as a careful and faithful perpetuation of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set 5/8" x 36" iron w/cap in Monument Box		
Nail w/tag Power Pole	N 38 W	51.38 ft.
Nail w/tag 12" Maple	N 60 W	55.63 ft.
center Phone Box	S 75 E	62.54 ft.
Stop sign post	N 75 E	53.05 ft.



Signed by *JA Bieszk* Date 25 November 1997
 Surveyor's Michigan License No. 41093