

SURVEY & REMONUMENTATION

KENT COUNTY REMONUMENTATION

MAR 03 1998

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in **SECTION**
KENT COUNTY

Located In: Corner Code #

1. Public Land Survey	T <u>6N</u> R <u>9W</u>	B-1
	T <u> </u> R <u> </u>	<u> </u>
	T <u> </u> R <u> </u>	<u> </u>
	T <u> </u> R <u> </u>	<u> </u>
2. Property Controlling in Section	S <u> </u> T <u> </u> R <u> </u>	<u> </u>
	S <u> </u> T <u> </u> R <u> </u>	<u> </u>
3. Miscellaneous Property in Sec.	S <u> </u> T <u> </u> R <u> </u>	<u> </u>
	S <u> </u> T <u> </u> R <u> </u>	<u> </u>

STATE OF MICHIGAN
COUNTY OF KENT
RECEIVED FOR RECORD
97 APR 29 AM 8:20
REG. OF DEEDS
Luis Standa

9792

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Kirk Breitels, in a field survey on Mar. 5, 1997 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A	B	C	D	E	F	G	H	I	J	K	L	M
1												
2	6	5	4	3	2	1						
3												
4	7	8	9	10	11	12						
5												
6	10	17	16	15	14	13						
7												
8	19	20	21	22	23	24						
9												
10	30	29	28	27	26	25						
11												
12	31	32	33	34	35	36						
13												

A. Description of original monument and accessories and/or subsequent restoration:

B-1	1830	GLO		Not Post
	1902-70	Williams & Works		Stone - Set Iron - Iron
	1972	LCRC #115	Spicer	"T" Iron
	1985	LCRC #4143	Rosema	Set Kent County Monument
	1991	LCRC #5816	Unema	Kent County Monument

The position of this corner was previously approved by the Kent County Remonumentation Peer Group, monumented by Maurice J. Rosema on 3-18-85 and was recorded per LCRC #4143

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:


B-1 Found standard Kent Co. Mon. (Harrison) per witnesses from above LCRC as set by Maurice J. Rosema on township line in place of the "T" Iron he found. Said "T" Iron checks with Williams & Works information and LCRC #115.

LCRC #4143	LCRC #5816
Nail & tag 12" Cherry N17°E 31.94'	Nail & tag 28" Oak N51°E 53.73'
Nail & tag 24" Oak N54°E 54.25'	Nail & tag 22" Oak S02°E 32.63'
Nail & tag 6" Oak S53°E 65.17'	Nail & tag 10" Oak S53°E 65.23'
Nail & tag 18" Oak S01°E 32.60'	Nail & tag wood post S47°W 55.08'
Nail & tag wood post S49°W 55.02'	KC Mon. (B-13, 7-9) East 89.12'

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence of the position of the corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

B-1 Standard Kent County Monument	
Nail & KC Remon. tag NW side 32" Oak	N51°E 53.73'
Nail & KC Remon. tag E. side 26" Oak	S02°E 32.63'
Nail & KC Remon. tag SW side 14" Oak	S53°E 65.25'
Nail & KC Remon. tag NW side 0.7' dia. wood post	S47°W 55.00'
Kent Co. Mon. (B-13, T7N, R9W)	East 89.12'
N-S Power lines (most E'ly line) is West 82'±	
On tree row to South	
C/L gravel road E-W is 3'± South	



Signed by Kirk Breitels
Surveyor's Michigan License No. 30077

Date 3/27/97

P.A. 345 1990 KENT COUNTY
PEER APPROVED 3/27/97
CHAIRMAN [Signature]