

SURVEY & REMONUMENTATION

MAR 03 1998

KENT COUNTY REMONUMENTATION

SECTION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

STATE OF MICHIGAN
COUNTY OF KENT
RECEIVED FOR RECORD
97 APR 29 AM 8:22
REG. OF DEEDS

For corners in
KENT COUNTY

Located In: Corner Code #

1. Public Land Survey	T <u>6N</u> R <u>9W</u>	E-9
	T _____ R _____	_____
	T _____ R _____	_____
	T _____ R _____	_____
2. Property Controlling in Section	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____
3. Miscellaneous Property in Sec.	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____

9824

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

A	B	C	D	E	F	G	H	I	J	K	L	M
1												
2	6	5	4	3	2							
3												
4	7	8	9	10	11	12						
5												
6	18	17	16	15	14	13						
7												
8	19	20	21	22	23	24						
9												
10	30	29	28	27	26	25						
11												
12	31	32	33	34	35	36						
13												

I, Kirk Breitels, in a field survey on Jan. 7, 1997 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

E-9	1830	GLO	Mullett	Set Post
		Kent Co. Wit.		"X" in pavement
	1978	LCRC #1190	Merdzinski	PK Nail & MSHD tag
	1981	LCRC #2472	Jonker	Set Kent County Monument
	1995	LCRC #8198	Breitels	Kent County Monument

The position of this corner was previously approved by the Kent County Remonumentation Peer Group, monumented by Robert J. Jonker on 11/25/81 and was recorded per LCRC #2472.


B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
E-9 Found standard Kent Co. Mon. (Harrison) per witnesses from above LCRC as set by Robert J. Jonker in place of the PK Nail & MSHD tag he found. Said PK Nail & tag checks with Kent Co. Wit. & LCRC #1190.

LCRC #2472		LCRC #8198	
SE cor. conc. hdwl.	N36°E 28.55'	SE cor. conc. hdwl.	N36°E 28.55'
Remon. tag side 18" Oak	N39°E 41.70'	Nail & tag 28" Oak	N39°E 41.76'
Remon. tag Power Pole	S44°W 62.62'	Nail & tag guard post	S33°E 29.22'
Remon. tag guard post	S33°E 29.13'	Nail & tag guard post	S02°E 41.89'
Remon. tag guard post	S02°E 41.78'	Nail & tag 20" Oak	S40°W 69.20'

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

E-9 Standard Kent County Monument	
SE cor. concrete headwall	N36°E 28.55'
Nail & KC Remon. tag NW side 28" Oak	N39°E 41.76'
Nail & KC Remon. tag E. side guard post	S33°E 29.22'
Nail & KC Remon. tag E. side guard post	S02°E 41.89'
New nail & KC Remon. tag E. side 24" Oak	S40°W 69.48'
C/L N-S gravel roads, West 12' m/l	
C/L traveled way, South 0.6' m/l	



Signed by Kirk Breitels
Surveyor's Michigan License No. 30077

Date 3/27/97

P.A. 345 1990 KENT COUNTY

PEER APPROVED 3/27/97

CHAIRMAN [Signature]

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983
REVISED OCT., 1985