

SURVEY & REMONUMENTATION

MAR 03 1998

KENT COUNTY REMONUMENTATION

SECTION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

STATE OF MICHIGAN
COUNTY OF KENT
RECEIVED FOR RECORD
97 JUN -3 AM 8:11
REG. OF DEEDS
Lucy Spauld

9993

Register of Deeds Stamp & File Number

For corners in
KENT COUNTY
(County)

Located In:	Corner Code #
T 6N R 9W	H-13
T R	
T R	
T R	
T R	
S T R	
S T R	
S T R	
S T R	

1. Public Land Survey

2. Property Controlling in Section

3. Miscellaneous Property in Sec.

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2				
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

I, Kirk Breitels, in a field survey on May 15, 1997 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Date	LCRC #	Surveyor	Monument
1830	GLO	Mullett	Set Post
1982	LCRC #2889	Jonker	3/4" Rerod
1982	LCRC #3092	Jonker	Set Kent County Monument
1990	LCRC #5472	Starr	Kent County Monument

The position of this corner was previously approved by the Kent County Remonumentation Peer Group, monumented by Robert J. Jonker on 9/17/82 and was recorded per LCRC #3092

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

H-13 Found standard Kent Co. Mon. (Harrison) per witnesses from above LCRC as set by Robert J. Jonker in place of the 3/4" x 16" Rerod he found. Said Rerod checks with LCRC #2889.

LCRC #3092	LCRC #5472
Remon. tag Fc. Post N00°E 27.5'	Nail & tag Fc. Post N00°E 27.58'
Remon. tag P. Pole S80°W 107.0'	Nail & tag P. Pole S80°W 107.15'
Chiseled "X" culv. N70°E 50.08'	Chiseled "X" on culv. N70°E 69.80'
NE cor. conc. fnd. S00°E 75.85'	NE cor. conc. fnd. S00°E 75.89'
PK Nail top Fc. Post S60°E 66.00'	Nail & tag in wood post S55°E 70.66'
	Nail & tag 10" Maple N70°W 87.27'


The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Description	Measurement
H-13 Standard Kent County Monument	
Nail & KC Remon. tag N. side P. Pole	S80°W 107.11'
Chiseled "X" on top N. end concrete culvert	N70°E 60.05'
NE corner concrete foundation	S00°E 75.89'
Nail & KC Remon. tag SW side wood post	S55°E 70.85' post leaning SE
Nail & KC Remon. tag W. side top wood fc. post	N00°E 34.62'
Nail & KC Remon. tag S. side Twin 10" Elm	N70°W 98.97'
C/L E-W asphalt road is North 3'±	
On fence line to North ±	

Signed by *Kirk Breitels*
Surveyor's Michigan License No. 30077

Date 5/22/97



P.A. 345 1990 KENT COUNTY

PEER APPROVED 5/22/97

CHAIRMAN *Harry Wheeler*