

SURVEY & REMONUMENTATION

MAR 03 1998

KENT COUNTY REMONUMENTATION

STATE OF MICHIGAN
COUNTY OF KENT
RECEIVED FOR RECORD

97 APR 29 AM 8:27

SECTION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

W. J. Bond
REG. OF DEEDS

For corners in

<u>KENT COUNTY</u> (County)	Located In:	Corner Code #
1. Public Land Survey	T <u>6N</u> R <u>9W</u>	<u>L-1</u>
	T <u> </u> R <u> </u>	<u> </u>
	T <u> </u> R <u> </u>	<u> </u>
	T <u> </u> R <u> </u>	<u> </u>
2. Property Controlling in Section	S <u> </u> T <u> </u> R <u> </u>	<u> </u>
	S <u> </u> T <u> </u> R <u> </u>	<u> </u>
3. Miscellaneous Property in Sec.	S <u> </u> T <u> </u> R <u> </u>	<u> </u>
	S <u> </u> T <u> </u> R <u> </u>	<u> </u>

9882

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

I, Kirk Breitels, in a field survey on Jan. 16, 1997 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

L-1	1830	GLO		Not Set
	1957	Williams & Works		Iron Pipe
	1959	Kent Co. Wit.		Stake, Stone & Crockery
	1975	LCRC #901	Fluharty	"T" Iron
	1991	LCRC #5771	Chettleburgh	Set Kent County Monument
	1995	LCRC #8291	Byl	Kent County Monument

The position of this corner was previously approved by the Kent County Remonumentation Peer Group, monumented by Thomas M. Chettleburgh on 3/5/91 and was recorded per LCRC #5771.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

L-1 Found standard Kent Co. Mon. (Harrison) per witnesses from above LCRC as set by Thomas M. Chettleburgh in place of the "City Iron" and "T" Iron (0.19' N. & 0.13' E. of City Iron) he found. Both Irons check with Williams & Works and LCRC #901

LCRC #5771	L-13, 7-9 East	48.78'	LCRC #8291	L-1, 7-9 N90°E	48.78'
Remon. tag 10" Oak	N35°E	70.83'	Nail/tag 14" Oak	N35°E	70.67'
Remon. tag 24" Walnut	S82°E	70.07'	Nail/tag 28" Walnut	S82°E	70.00'
Remon. tag 16" Maple	S82°E	19.91'	Nail/tag 20" Maple	S82°E	19.82'
Remon. tag PP S49°W	61.84'	Remon. tag	Nail/tag PP S62°E	100.33'	Nail/tag PP
Remon. tag PP N64°W	48.10'	PP S62°E	100.38'	Nail/tag PP N65°E	90.03'
					S75°W 51.90'


The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence of the position of the corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

L-1 Standard Kent County Monument

Nail & KC Remon. tag W. side	14" Oak	N35°E	70.62'
Nail & KC Remon. tag N. side	28" Walnut	S82°E	70.00'
Nail & KC Remon. tag N. side	20" Maple	S82°E	19.82'
Nail & KC Remon. tag NE side	Power Pole	S62°E	100.33'
Nail & KC Remon. tag N. side	Power Pole	S75°W	51.90'
Nail & KC Remon. tag NE side	Power Pole	S65°E	90.03'
L-13 (T7N, R9W - Kent Co. Mon.)		N90°E	48.69'

E. edge of pvmt. is E. 12.5'±; N. edge of pvmt. is N. 33.0'±



Signed by *Kirk Breitels*
Surveyor's Michigan License No. 30077

Date 3/27/97

P.A. 345 1990 KENT COUNTY
PEER APPROVED 3/27/97
CHAIRMAN *Harry Hubert*