

# LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A. 1970

MARQUETTE COUNTY

FOR CORNERS OF --:	LOCATED IN --:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 46 N. 28 <input checked="" type="checkbox"/> R. <input checked="" type="checkbox"/> W.	C5, C4
2. PROPERTY CONTROLLING IN SECTION - 8	T. 46 N. 28 <input checked="" type="checkbox"/> R. <input checked="" type="checkbox"/> W.	3, 10
3. MISCELLANEOUS PROPERTY IN SECTION	T. 1 N. S. R. W.	
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Keith L. Sackett, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on see below, 19\_\_\_\_, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on \_\_\_\_\_, 19\_\_\_\_, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

**A. Description of original monument and accessories and/or subsequent restoration:**

- Corner C5: Original monument and accessories not found.
- Corner C4: Original monument and accessories not found.
- Corner 3: Not set on original survey nor subsequently apparently.
- Corner 10: Not set on original survey nor subsequently apparently.

**B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:**

- Corner C5: Restored 10-17-83 by double proportion; checks good with swamp call and pine stump north. Fits good with swamp call south.
- Corner C4: Restored 10-20-83 midway and on line between section corners north and south.
- Corner 3: Established 10-20-83 midway and on line between corners north and south.
- Corner 10: Established 10-20-83 midway and on line between corners north and south.

**C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:**

- |   |  |
|---|--|
| Corner C5: Set 1" I.D. by 32" I.P. w/4" alum. cap.<br>16" red pine S82W 13.2 ft. S18, NBT<br>4" maple N26W 5.3 ft. S7, NBT<br>12" red pine S72E 16.8 ft. S17, NBT | Corner 3: Set 1" I.D. by 32" I.P. w/4" alum. cap.<br>18" w. pine S29E 23.6 ft. 1/16S, BT<br>30" w. pine N87E 40.4 ft. 1/16S, BT<br>16" w. pine N82W 39.4 ft. 1/16S, BT |
| Corner C4: Set 1" I.D. by 32" I.P. w/4" alum. cap.<br>26" w. pine S80E 86.6 ft. 1/4S, NBT<br>5" spruce S65W 20.5 ft. 1/4S, NBT                                    | Corner 10: Set 1" I.D. by 32" I.P. w/4" alum. cap.<br>5" spruce N65W 12.5 ft. 1/16S, BT<br>4" spruce N15E 12.5 ft. 1/16S, BT<br>7" spruce S03E 19.8 ft. 1/16S, BT      |

SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_

SURVEYOR'S MICHIGAN REGISTRATION NO. \_\_\_\_\_

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_

APPROVED AND SIGNED BY Keith L. Sackett DATE 11-28-83  
CHIEF OF SURVEY PARTY  
MICHIGAN REGISTERED LAND SURVEYOR

**Keith L. Sackett**  
 Michigan Department of Natural Resources

SURVEYOR'S MICHIGAN REGISTRATION NO. 19006