

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--:	LOCATED IN--:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 30 N. R. 2 E.	F-13; I-13; K-13
2. PROPERTY CONTROLLING IN SECTION	T. N. S. R. E. W.	
3. MISCELLANEOUS PROPERTY IN SECTION	T. N. S. R. E. W.	
4. LOT NO., RECORDED PLAT.		
5. PRIVATE CLAIMS		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Kenneth J. Ostling, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on June 30, 1977, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law;

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:


- F-13 Set corner by proportionate measurement between section corners. Old fence corner N & E is about 20' west but could find no solid support for that position. No U.S. evidence.
- I-13 Found corner as established by G.F. DeLaMater survey and used in subsequent surveys by Leo Smith, D. Marlatt, G. Henning & others. Found and used in 1960 survey by this dept.
- K-13 Corner previously found in 1960 DNR survey. Found old post at proper position west of 1/2" bar which we conclude to be closing corner. Previsouly found and noted by F. Smith in 1941 survey.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

F-13	I-13	K-13
Set DNR mon. & red-top post	Left conc. mon. in place	Set new DNR mon. & cedar post
5" Maple N30°E 13.10	set cedar post	12" Oak N37°E 15.6
5" W. Oak N22°W 31.55	8" Oak S82°W 34.1	2" Spruce N35°W 35.0
N 1/4 Sec. 4 T29N R2E	9" Oak S25°E 24.7	NE corner Sec. 2, T29N, R2E
East 16.20	NE corner Sec. 3 T29N R2E	is 14.57 E
	is 19.6' East	

SIGNED BY Kenneth J. Ostling DATE 7/10/77

SURVEYOR'S MICHIGAN REGISTRATION NO. 10068



FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR (SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____ MONTMORENCY COUNTY

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET