

APR 29 1996

JUDITH D. RDEHM
 Ontonagon County
 LC 3/ 372 MEL Fee: 9.00
 10/26/95
 14:10
 Page 1 of 1

COMMISSION LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in ONTONAGON Located in: _____ Corner Code # _____
 (County)

- | | | | | | | |
|--------------------------------------|---|-----------|---|-----------|-------------|-------|
| 1. Public Land Survey | T | <u>49</u> | R | <u>42</u> | <u>C-12</u> | |
| | T | _____ | R | _____ | _____ | |
| | T | _____ | R | _____ | _____ | |
| | T | _____ | R | _____ | _____ | |
| 2. Property Controlling in Section | S | _____ | T | _____ | R | _____ |
| | S | _____ | T | _____ | R | _____ |
| 3. Miscellaneous Property in Section | S | _____ | T | _____ | R | _____ |
| | S | _____ | T | _____ | R | _____ |

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
 5. Private Claims _____

$\frac{1}{4}$ Corner common to Section 31 & 32, T49N R42W.

I, Earl W. Applekamp, in a field survey on August 30, 19 95, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Professional Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1						
3												
4	7	8	9	10	11	12						
5												
6	18	17	16	15	14	13						
7												
8	19	20	21	22	23	24						
9												
10	30	29	28	27	26	25						
11												
12	31	32	33	34	35	36						
13												

A. Description of original monument and accessories and/or subsequent restoration:

Original corner established by William Burt, U.S. Deputy Surveyor, June 14, 1848. Set Sugar Post.

ORIGINAL BEARING TREES:

Sugar 8" S70°E 54 links (35.64 feet)
 Sugar 24" N65W 46 links (30.36 feet)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

No original evidence was found. Corner was re-established by single proportionate measurement between opposite section corners to the North and South.


Research on file with County Remonumentation Program Representative.

PEER GROUP APPROVED
Earl W. Applekamp 10-18-95
 COUNTY REPRESENTATIVE

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

At the corner position I set a 2 $\frac{1}{2}$ "x30" aluminum pipe with a 3 $\frac{1}{4}$ " cap stamped to read: T49N R42W, $\frac{1}{4}$, S.31, S.32, 1995, P.S. 17610. I established the following bearing trees and reference objects:

12" Maple N56°W 39.90 feet - 11" Maple N62°E 36.71 feet
 7" Maple S19°W 21.37 feet - Steel Sign Post South 1.47 feet



Signed by Earl W. Applekamp
 Surveyor's Michigan License No. 17610

Date October 03, 1995