



ST. CLAIR COUNTY, MICHIGAN  
OFFICIAL GOVERNMENT CORNER

SURVEY &  
REMONUMENTATION

MAR 15 2000

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

SECTION

CLERK REGISTER  
ST. CLAIR COUNTY  
RECEIVED FOR RECORD

DEC 22 1999

LIBER PAGE TIME

*Marilyn Dunn*  
MARILYN DUNN

Register of Deeds Stamp & File Number

	Located In:	Corner Code #
	COLUMBUS TOWNSHIP	J-13
1. Public Land Survey	T 5N R 15E	J-13
	T _____ R _____	_____
2. Property Controlling in Section	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____
3. Miscellaneous Property in Sec.	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____
4. Lot No. _____, Recorded Plat _____		
5. Private Claims _____		

I, MICHAEL J. ROSSOW, in a field survey on JULY 13, 1999, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

NOTE: Not more than 1 CORNER, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

- J-13, COLUMBUS TOWNSHIP, 1817, W. PRESTON OF GLO (MADE CORNER ON 3" ELM TREE)
- (A) 1986, R. KREGER LCRC L.5, P.317 (CORNER REMOVED, REPLACED & WITNESSES SAME; NO MENTION OF POINT SET)
- (B) 1986, J. LANSKY SURVEY L.9, P.382 (FINDS & USES "PK NAIL", NO WITNESSES MENTIONED)
- (C) 1986, J. LANSKY SURVEY L.16, P.389 (REFERS TO CORNER NO ID & NO WITNESSES)
- (D) 1942, OLD COUNTY SURVEYORS MAP (FIND & WITNESSES A 1" IRON ROD UNDER BLACK TOP)
- (E) ST. CLAIR COUNTY ROAD COMMISSION PLANS OF 07-07-1993 (FIND PK NAIL & WITNESSES)
- (F) ST. CLAIR COUNTY ROAD COMMISSION WITNESS BOOK, 1986 (R. KREGER REFERS TO OFFSET)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND A STANDARD MONUMENT BOX IN PAVEMENT WITH PK NAIL INSIDE, USING SURVEY L.9, P.382 & LCRC L.5, P.317 IN PART "A" ABOVE THE POINT WAS VERIFIED AND ACCEPTED AS THE CORNER WITH THE FOLLOWING DATA RECORDED:

- 70.44' SOUTH EAST SPIKE IN CORNER OF FENCE POST (A)
- 98.04' WEST NORTH WEST TO SPIKE IN DETROIT EDISON POLE (A)
- FENCE LINE OCCUPATION LINE NORTH (A)
- 87.3' SOUTH EAST TO SPIKE IN HICKORY (F)(A)
- 78.04' NORTH WEST TO PK IN DETROIT EDISON POLE (F)
- 38.22' WEST OF NORTH 1/4 CORNER OF SECTION 6, T.4N, R.15E. (E)(F)(A)

PA 345-1990  
PEER COMMITTEE  
APPROVED 12-15-99


C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

SET A 1/2" DIAMETER REROD AND ALSO SET A 2" DIAMETER ALUMINUM CAP WITH MAGNET ATTACHED & INSCRIBED "ST. CLAIR COUNTY OFFICIAL CORNER" ON THE 1/2" REROD & WITNESSED AS FOLLOWS:

- EAST NORTH EAST 82.5' TO COUNTY TAG IN GUARD RAIL POST
- EAST SOUTH EAST 84.6' TO COUNTY TAG IN GUARD RAIL POST
- WEST SOUTH WEST 185.01' TO COUNTY TAG IN 10" TREE
- WEST NORTH WEST 98.12' TO COUNTY TAG IN POWER POLE

THE SELECTED LOCATION IS ACCEPTED BY ME AND IS GENERALLY ACCEPTED BY PROFESSIONAL SURVEYORS AS THE BEST AVAILABLE EVIDENCE OF THE POSITION OF THE ORIGINAL CORNER



Signed by 

Date 12-17-99

Surveyor's Michigan License No. 24615